


SHCSTM 200

Normal-Duty Take-Up Unit
Wide Inner Ring
Eccentric Lock


Seal Styles




Standard Seal with Flinger



Triple-Lip L3 Seal





Bearing Number	Shaft Dia. d in. mm.	Dimensions in. mm. O	G	P	Q	S	B	K	E	A	W	J	L	H	Bi	N	M	Load Rating lbs. kN. Dynamic Cr	Static Cor	Bearing Insert	Housing Number	Weight lbs. kg.
SHCSTM 204-12	3/4	0.63	0.38	2.00	1.25	0.75	2.00	0.53	3.00	3.50	3.70	1.25	0.83	2.40	1.7205	0.6732	0.6732	2,331	1,142	SHC 204-12	STM 204	2.0
SHCSTM 204	20	16.0	10.0	51.0	32.0	19.0	51.0	13.5	76.0	89.0	94.0	32.0	21.0	61.0	43.7	17.1	17.1	10.37	5.08	SHC 204		0.9
SHCSTM 205-14	7/8																			SHC 205-14		
SHCSTM 205-15	15/16	0.63	0.38	2.00	1.25	0.75	2.00	0.53	3.00	3.50	3.82	1.25	0.94	2.44	1.7480	0.6890	0.6890	2,542	1,349	SHC 205-15	STM 205	2.2
SHCSTM 205	25	16.0	10.0	51.0	32.0	19.0	51.0	13.5	76.0	89.0	97.0	32.0	24.0	62.0	44.4	17.5	17.4	11.31	6.00	SHC 205		1.0
SHCSTM 205-16	1																			SHC 205-16		
SHCSTM 206-17	1 1/16																			SHC 206-17		
SHCSTM 206-18	1 1/8																			SHC 206-18		
SHCSTM 206	30	0.63	0.44	2.20	1.46	0.87	2.25	0.53	3.50	4.02	4.45	1.46	1.10	2.75	1.9055	0.7205	0.7165	3,554	1,942	SHC 206	STM 206	3.3
SHCSTM 206-19	1 3/16	16.0	11.0	56.0	37.0	22.0	57.0	13.5	89.0	102.0	113.0	37.0	28.0	70.0	48.4	18.3	18.2	15.81	8.64	SHC 206-19		1.5
SHCSTM 206-20	1 1/4																			SHC 206-20		
SHCSTM 207-20	1 1/4																			SHC 207-20		
SHCSTM 207-21	1 5/16																			SHC 207-21		
SHCSTM 207-22	1 3/8	0.63	0.56	2.52	1.46	0.87	2.52	0.53	3.50	4.02	5.12	1.46	1.18	3.07	2.0118	0.7402	0.7402	4,683	2,626	SHC 207-22	STM 207	4.2
SHCSTM 207	35	16.0	14.0	64.0	37.0	22.0	64.0	13.1	89.0	102.0	130.0	37.0	30.0	78.0	51.1	18.8	18.8	20.83	11.68	SHC 207		1.9
SHCSTM 207-23	1 7/16																			SHC 207-23		
SHCSTM 208-24	1 1/2																			SHC 208-24		
SHCSTM 208-25	1 9/16	0.75	0.67	3.27	1.94	1.13	3.27	0.63	4.02	4.50	5.67	1.93	1.30	3.476	2.2165	0.8425	0.8425	5,293	3,057	SHC 208-25	STM 208	6.2
SHCSTM 208	40	19.0	17.0	83.0	49.0	29.0	83.0	16.0	102.0	114.0	144.0	49.0	33.0	88.0	56.3	21.4	21.4	23.55	13.60	SHC 208		2.8
SHCSTM 209-26	1 5/8																			SHC 209-26		
SHCSTM 209-27	1 11/16	0.75	0.67	3.27	1.94	1.13	3.27	0.63	4.02	4.61	5.71	1.93	1.38	3.43	2.2165	0.8425	0.8425	5,924	3,507	SHC 209-27	STM 209	6.9
SHCSTM 209-28	1 3/4	19.0	17.0	83.0	49.0	29.0	83.0	16.0	102.0	117.0	145.0	49.0	35.0	87.0	56.3	21.4	21.4	26.35	15.60	SHC 209-28		3.1
SHCSTM 209	45																			SHC 209		
SHCSTM 210-30	1 7/8																			SHC 210-30		
SHCSTM 210-31	1 15/16	0.75	0.67	3.27	1.94	1.13	3.39	0.63	4.02	4.61	5.91	1.93	1.46	3.54	2.4685	0.9685	0.9685	6,402	4,046	SHC 210-31	STM 210	7.1
SHCSTM 210	50	19.0	17.0	83.0	49.0	29.0	86.0	16.0	102.0	117.0	150.0	49.0	37.0	90.0	62.7	24.6	24.6	28.48	18.00	SHC 210		3.2
SHCSTM 210-32	2																			SHC 210-32		
SHCSTM 211-32	2																			SHC 211-32		
SHCSTM 211-34	2 1/8	0.98	0.75	4.02	2.52	1.38	3.75	0.87	5.12	5.71	6.73	2.52	1.50	4.17	2.8110	1.0945	1.0906	7,931	5,036	SHC 211-34	STM 211	10.7
SHCSTM 211	55	25.0	19.0	102.0	64.0	35.0	95.0	22.0	130.0	146.0	171.0	64.0	38.0	106.0	71.4	27.8	27.7	35.28	22.40	SHC 211		4.9
SHCSTM 211-35	2 3/16																			SHC 211-35		
SHCSTM 212-36	2 1/4																			SHC 212-36		
SHCSTM 212	60	1.26	0.75	4.02	2.52	1.38	4.02	0.87	5.12	5.71	7.64	2.52	1.65	4.69	3.0630	1.2205	1.2165	9,554	5,921	SHC 212	STM 212	13.1
SHCSTM 212-38	2 3/8	32.0	19.0	102.0	64.0	35.0	102.0	22.0	130.0	145.0	194.0	64.0	42.0	119.0	77.8	31.0	30.9	42.50	26.34	SHC 212-38		6.0
SHCSTM 212-39	2 7/16																			SHC 212-39		

MARINER®

Mariner stainless steel mounted bearings are a product of Baart Industrial Group (Baart). While Baart has tried to ensure the accuracy of the information contained in this document, Baart accepts no responsibility for inaccurate in, or changes to, such information. All rights reserved. ©2020