


SUCSPAM 200

Normal-Duty Tapped-Base Pillow Block Setscrew Lock

Seal Styles



Permanent Lubrication



Bearing Number	Shaft Dia. d in. mm.	Dimensions in. mm. H	A	E	B	R	G	W	Bi	N	M	Thread Size (T) in. mm.	Load Rating lbs. kN. Dynamic Cr	Static Cor	Bearing Insert	Housing Number	Wt. lbs. kg.
SUCSPAM 201L4L	12	1.313 33.3	2.88 73.0	2.000 50.8	1.50 38.0	0.50 12.7	0.44 11.0	2.56 65.0	1.2205 31.0	0.5000 12.7	0.7205 18.3	3/8-16	2,331 10.37	1,142 5.08	SUC 201	SPAM 204	1.6 0.7
SUCSPAM 201-8L4L	1/2														SUC 201-8		
SUCSPAM 202L4L	15														SUC 202		
SUCSPAM 202-10L4L	5/8														SUC 202-10		
SUCSPAM 203L4L	17														SUC 203		
SUCSPAM 204-12L4L	3/4														SUC 204-12		
SUCSPAM 204L4L	20														SUC 204		
SUCSPAM 205-14L4L	7/8	1.438 36.5	3.00 76.0	2.000 50.8	1.50 38.0	0.50 12.7	0.47 12.0	2.80 71.0	1.3425 34.1	0.5630 14.3	0.7795 19.8	3/8-16	2,542 11.31	1,349 6.00	SUC 205-14	SPAM 205	2.0 0.9
SUCSPAM 205-15L4L	15/16														SUC 205-15		
SUCSPAM 205L4L	25														SUC 205		
SUCSPAM 205-16L4L	1														SUC 205-16		
SUCSPAM 206-17L4L	1 1/16	1.688 42.9	4.00 102.0	3.000 76.2	1.50 38.0	0.63 16.0	0.47 12.0	3.43 87.0	1.5000 38.1	0.6260 15.9	0.8740 22.2	7/16-14	3,554 15.81	1,942 8.64	SUC 206-17	SPAM 206	3.1 1.4
SUCSPAM 206-18L4L	1 1/8														SUC 206-18		
SUCSPAM 206L4L	30														SUC 206		
SUCSPAM 206-19L4L	1 3/16														SUC 206-19		
SUCSPAM 206-20L4L	1 1/4														SUC 206-20		
SUCSPAM 207-20L4L	1 1/4	1.875 47.6	4.25 108.0	3.250 82.6	1.89 48.0	0.75 19.0	0.47 12.0	3.74 95.0	1.6809 42.9	0.6890 17.5	1.0000 25.4	1/2-13	4,683 20.83	2,626 11.68	SUC 207-20	SPAM 207	4.1 1.9
SUCSPAM 207-21L4L	1 5/16														SUC 207-21		
SUCSPAM 207-22L4L	1 3/8														SUC 207-22		
SUCSPAM 207L4L	35														SUC 207		
SUCSPAM 207-23L4L	1 7/16														SUC 207-23		
SUCSPAM 208-24L4L	1 1/2	1.938 49.2	4.63 117.0	3.500 88.9	1.89 48.0	0.75 19.0	0.47 12.0	3.94 100.0	1.9370 49.2	0.7480 19.0	1.1890 30.2	1/2-13	5,294 23.55	3,057 13.60	SUC 208-24	SPAM 208	5.1 2.3
SUCSPAM 208-25L4L	1 9/16														SUC 208-25		
SUCSPAM 208L4L	40														SUC 208		
SUCSPAM 209-26L4L	1 5/8	2.125 54.0	4.96 126.0	3.750 95.3	2.00 51.0	0.75 19.0	0.47 12.0	4.25 108.0	1.9370 49.2	0.7480 19.0	1.1890 30.2	1/2-13	5,923 26.35	3,507 15.60	SUC 209-26	SPAM 209	6.1 2.8
SUCSPAM 209-27L4L	1 11/16														SUC 209-27		
SUCSPAM 209-28L4L	1 3/4														SUC 209-28		
SUCSPAM 209L4L	45														SUC 209		
SUCSPAM 210-30L4L	1 7/8	2.250 57.2	5.50 140.0	4.000 101.6	2.00 51.0	0.87 22.0	0.55 14.0	4.61 117.0	2.0315 51.6	0.7480 19.0	1.2835 32.6	5/8-11	6,402 28.48	4,046 18.00	SUC 210-30	SPAM 210	7.0 3.2
SUCSPAM 210-31L4L	1 15/16														SUC 210-31		
SUCSPAM 210L4L	50														SUC 210		
SUCSPAM 210-32L4L	2														SUC 210-32		

LUBRILIFE™ MARINER®

Mariner stainless steel mounted bearings and Lubrilife permanent lubrication are products of Baart Industrial Group (Baart). While Baart has tried to ensure the accuracy of the information contained in this document, Baart accepts no responsibility for inaccurate in, or changes to, such information. All rights reserved. ©2020