


SUCSHAM 200


Normal-Duty Hanger Bearing Unit
Setscrew Lock

Seal Styles



Permanent Lubrication





Bearing Number	Shaft Dia. d in. mm.	Dimensions in. mm. A	W	C	H	L	D	K	Bi	N	M	Load Rating lbs. kN. Dynamic Cr	Static Cor	Bearing Insert	Housing Number	Wt. lbs. kg.
SUCSHAM 201L4L	12													SUC 201		
SUCSHAM 201-8L4L	1/2													SUC 201-8		
SUCSHAM 202L4L	15	2.52	3.78	0.00	2.52	1.57	0.75	PF 3/4	1.2205	0.5000	0.7205	2,331	1,142	SUC 202	SHAM 204	1.8
SUCSHAM 202-10L4L	5/8	64.0	96.0	0.0	64.0	40.0	19.0		31.0	12.7	18.3	10.37	5.08	SUC 202-10		0.8
SUCSHAM 203L4L	17													SUC 203		
SUCSHAM 204-12L4L	3/4													SUC 204-12		
SUCSHAM 204L4L	20													SUC 204		
SUCSHAM 205-14L4L	7/8													SUC 205-14		
SUCSHAM 205-15L4L	15/16	3.07	4.06	0.00	2.52	1.57	0.75	PF 3/4	1.3425	0.5630	0.7795	2,542	1,349	SUC 205-15	SHAM 205	2.0
SUCSHAM 205L4L	25	78.0	103.0	0.0	64.0	40.0	19.0		34.1	14.3	19.8	11.31	6.00	SUC 205		0.9
SUCSHAM 205-16L4L	1													SUC 205-16		
SUCSHAM 206-17L4L	1 1/16													SUC 206-17		
SUCSHAM 206-18L4L	1 1/8	3.07	4.06	0.00	2.52	1.57	0.75	PF 3/4	1.5000	0.6260	0.8740	3,554	1,942	SUC 206-18	SHAM 206	2.0
SUCSHAM 206L4L	30	78.0	103.0	0.0	64.0	40.0	19.0		38.1	15.9	22.2	15.81	8.64	SUC 206		0.9
SUCSHAM 206-19L4L	1 3/16													SUC 206-19		
SUCSHAM 206-20L4L	1 1/4													SUC 206-20		
SUCSHAM 207-20L4L	1 1/4													SUC 207-20		
SUCSHAM 207-21L4L	1 5/16	3.62	4.57	0.00	2.76	1.57	0.75	PF 3/4	1.6890	0.6890	1.0000	4,683	2,626	SUC 207-21	SHAM 207	2.6
SUCSHAM 207-22L4L	1 3/8	92.0	116.0	0.0	70.0	40.0	19.0		42.9	17.5	25.4	20.83	11.68	SUC 207-22		1.2
SUCSHAM 207L4L	35													SUC 207		
SUCSHAM 207-23L4L	1 7/16													SUC 207-23		
SUCSHAM 208-24L4L	1 1/2													SUC 208-24		
SUCSHAM 208-25L4L	1 9/16	3.78	4.76	0.08	2.87	1.57	0.75	PF 3/4	1.9370	0.7480	1.1890	5,294	3,057	SUC 208-25	SHAM 208	3.3
SUCSHAM 208L4L	40	96.0	121.0	2.0	73.0	40.0	19.0		49.2	19.0	30.2	23.55	13.60	SUC 208		1.5
SUCSHAM 209-26L4L	1 5/8													SUC 209-26		
SUCSHAM 209-27L4L	1 11/16	4.25	5.35	0.20	3.23	1.89	0.83	PF1	1.9370	0.7480	1.1890	5,923	3,507	SUC 209-27	SHAM 209	4.0
SUCSHAM 209-28L4L	1 3/4	108.0	136.0	5.0	82.0	48.0	21.0		49.2	19.0	30.2	26.35	15.60	SUC 209-28		1.8
SUCSHAM 209L4L	45													SUC 209		
SUCSHAM 210-30L4L	1 7/8													SUC 210-30		
SUCSHAM 210-31L4L	1 15/16	4.65	5.59	0.20	3.27	1.89	0.83	PF1	2.0315	0.7480	1.2835	6,402	4,046	SUC 210-31	SHAM 210	4.6
SUCSHAM 210L4L	50	118.0	142.0	5.0	83.0	48.0	21.0		51.6	19.0	32.6	28.48	18.00	SUC 210		2.1
SUCSHAM 210-32L4L	2													SUC 210-32		
SUCSHAM 211-32L4L	2													SUC 211-32		
SUCSHAM 211-34L4L	2 1/8	4.96	6.22	0.28	3.74	2.36	0.98	PF1 1/4	2.1890	0.8740	1.3150	7,931	5,036	SUC 211-34	SHAM 211	7.3
SUCSHAM 211L4L	55	126.0	158.0	7.0	95.0	60.0	25.0		55.6	22.2	33.4	35.28	22.40	SUC 211		3.3
SUCSHAM 211-35L4L	2 3/16													SUC 211-35		
SUCSHAM 212-36L4L	2 1/4													SUC 212-36		
SUCSHAM 212L4L	60	5.59	6.81	0.35	4.02	2.36	1.10	PF1 1/4	2.5630	1.0000	1.5630	9,554	5,921	SUC 212	SHAM 212	8.1
SUCSHAM 212-38L4L	2 3/8	142.0	173.0	9.0	102.0	60.0	28.0		65.1	25.4	39.7	42.50	26.34	SUC 212-38		3.7
SUCSHAM 212-39L4L	2 7/16													SUC 212-39		

LUBRILIFE™ MARINER®

Mariner stainless steel mounted bearings and Lubrilife permanent lubrication are products of Baart Industrial Group (Baart). While Baart has tried to ensure the accuracy of the information contained in this document, Baart accepts no responsibility for inaccurate in, or changes to, such information. All rights reserved. ©2020